

Workholding 2 + 2 Jaw Double Clamping Power Chuck



- Closed center style Power Chucks with 2 separate clamping motions of opposing jaws
- Ideal for square or angular work
- Long jaw stroke and high clamping forces
- A mounts
- Requires double acting cylinder
- 3mm serration pitch

Model No.	Jaw Stroke Dia.	Sleeve Stroke	Gripping Capacity		Draw Bar Pull (lb/f)	Grip Force (lb/f)	Max RPM	Weight (lbs)
			Max	Min				
20-688-10A6Z	.630	.866	10.0	1.574	5,070	18,500	2000	110
20-688-10A8Z	.630	.866	10.0	1.574	5,070	18,500	2000	110
20-688-12A8Z	.630	.866	12.0	1.574	5,070	18,500	1500	139
20-688-12A11Z	.630	.866	12.0	1.574	5,070	18,500	1500	139
20-688-15A8Z	.669	.984	15.0	2.047	6,600	23,800	1200	264
20-688-15A11Z	.669	.984	15.0	2.047	6,600	23,800	1200	264

Dimensional Data

MODEL	10	12	15
A	10.63	11.98	15
B	4.33	4.33	5.01
C	4.72	5.51	7.68
F	.217	.217	.295
H	6.693	6.673	9.252
J	2.283	2.283	3.071
K	4-M16	4-M16	4-M20
L	.945	.945	1.181
M	1.181	1.181	1.496
N	max min	2.520 2.205	3.071 2.736
O	max min	3.740 2.913	5.689 3.563
P	max min	.925 .059	1.319 .197
Q	1.574	1.574	1.968
R	.630	.630	.709
S	.122	.122	2.163
T	M42x1.5	M42x1.5	M55x2.0
U	.197	.197	.197
V	4.055	4.055	5.118
W	M16x20	M16x20	M20x25

